



Direct Vent Steel Stoves

MAJESTIC 

Direct Vent Steel Stoves

Add the traditional look and warmth of a stove to any room with our wide selection of direct vent stoves from Majestic. These direct vent stoves combine the heritage appeal of fine craftsmanship with the convenience of contemporary technology to ensure optimal functionality and timeless beauty.



SS38DVB direct vent stove with Black three piece glass door frame

Give people a place to gather – make fire the focal point of your room again with a direct vent steel stove from Majestic.



SS38DVG Direct vent stove with Gold one piece glass door frame

THE STRATFORD BAY DIRECT VENT STEEL STOVE

The SS38DV gas stove from Majestic adds traditional warmth and elegance to any decor. Its large bay window provides an unobstructed, panoramic view of the bright, dancing flames and the latest direct vent technology ensures clean burning efficient operation. Easily installed into almost any room, the SS38DV is a beautiful, convenient and easy to operate addition to any home.

THE FAIRFIELD FREESTANDING DIRECT VENT STEEL STOVE

With its contemporary style and traditional warmth, the Fairfield will add the natural beauty of fire to any room. Available with up to 30,000 BTUs, the Fairfield offers optional remote controls, allowing you to operate your stove from anywhere in the room. When you choose the 34 inch model with its window of three-sided ceramic glass – you'll be impressed with the Fairfield's durable warmth and timeless beauty.



Fairfield Direct Vent RFSDV34 with Charcoal Gray three-sided ceramic glass

STANDARD FEATURES:

SS38DV:

- Bay window design
- 316 square inches of viewing area
- Thermal efficiency up to 80%
- Battery operated pilot ignitor
- Variable flame control
 - 27,000 to 38,000 Btu/hr input (natural gas)
 - 25,000 to 35,000 Btu/hr input (propane gas)
- Standard heat activated blower with variable speed control
- Millivolt system operates in power outage
- Available in Natural Gas or Propane models
- Featuring the exclusive LexFire Burn System™ with realistically detailed full size logs, rich glowing surfaces and a large ember bed replicating the soft glow of a dying fire
- Black three piece glass or Gold one piece glass door options
- CSA design certified

RFSDV34:

- 30,000 BTUs natural gas and propane
- Charcoal Gray color
- Total System Control (TSRN, TSRP) features all-in-one valve construction, no additional fan or remote system required
- Exclusive Insta-Flame Radiant Ceramic Burner
- Six authentic "split oak" logs
- Three-sided ceramic glass viewing window

LEXFIRE BURN SYSTEM™

Exclusive LexFire Burn System™ – combines all of the elements of a natural wood fire to produce flames so realistic, you'll forget it's not real wood.

Realistic Logs – starting with hand carved samples that are perfectly proportioned to fit the stove size and viewing area and then color enhanced to match real wood.

Yellow Flames – bright yellow flames appear almost translucent in color.

Log glow – as log surfaces heat up they produce a bright reddish orange glow, similar to wood in the secondary stages of combustion.

Ember Bed – a large area of burning ember replicates the look of wood in the final stages of combustion.

Primary Combustion Zone – primary combustion of fuel load.

LexFire Burn – gas and oxygen are precisely metered and strategically distributed to provide optimum flame presentation.

Direct Vent Steel Stoves

Model	SS38DV	RFSDV34
BTU / HR	27,000 - 38,000 NG / 25,000 -35,000 LP	21,000 - 30,000 NG / 22,500 - 30,000 LP
FE Ratings (Fireplace Efficiency)	80.1% NG / 81.8% LP	Up to 72.1%
Afue Efficiency	–	Up to 70%
Thermal Efficiency	Up to 80%	83% NG / 84% LP
Dimensions (Actual)	26 1/2"W x 17"H x 31 1/2"D	26 1/4"W x 31 1/2"H x 19 3/8"D
Fire Viewing Area (Sq. inch)	316	–
Flue Size (Inches)	4" x 6.625"	–
Fan	160 CFM	–
Heating Capacity (Sq. ft.)	1,800	–
Shipping Weight (Lbs.)	170	–

Note: Square foot heating capacities are approximations only. They will vary depending upon the level of insulation, climate, house design, ceiling height, ambient outside temperatures and how the appliance is operated. Tested to Canadian Standards Association's CSAP.4.1-02 testing method for measuring fireplace efficiency.

Optional Accessories

SS38DV OPTIONS

- Black Door Frame with Three Piece Glass
- Gold Door Frame with One Piece Glass
- Conversion Kits
 - NG to LP Conversion Kit
 - LP to NG Conversion Kit
 - High Altitude Conversion Kit

RFSDV34 OPTIONS

- Antique or Pewter window trim & flue rings
- Polished Brass window trim (flue rings extra)

Also Available:

- Charcoal Gray, Polished Brass or Pewter flue rings
- Natural vent flue adaptor



Multi-functional Ambient Technologies® remote controls available for all units



Programmable wireless wall thermostat with receiver



Touch screen hand held ON/OFF remote

See our Ambient Technologies® catalog for a complete line of remotes and thermostats.

For more information about MHSC and Majestic efficient and environmentally friendly products, please visit www.majesticproducts.com



Tested & Listed By



MAJESTIC

A Brand of Monessen Hearth Systems Co.
149 Cleveland Drive, Paris, Kentucky 40361
www.majesticproducts.com

Your Majestic Dealer:

To avoid personal injury or property damage, the product described by this brochure must be installed, operated and maintained in strict compliance with the instructions packaged with the product and all applicable building or fire codes. Contact local building or fire officials about restrictions and installation inspection requirements. All photographs and drawings on this brochure are for illustrative purposes only and are not intended for, nor should they be used as a substitute for the instructions packaged with the unit. Appearance and specifications of the product are subject to change without notice. © 2010 Monessen Hearth Systems Co.